BF SUBLISTOP80

CAD CAM



PRODUCT DESCRIPTION

BF SUBLISTOP80 was developed to be applied on sublimated polyester garments. With a thickenss of just 80 microns, we added a built-in blocker to the polyurethane film to stop the dye migration process. This product can withstand multiple wash cycles. Thanks to the highly visible cutting lines and the ease of use, you can rest assured that this product will increase your productivity.

BF SUBLISTOP80 features a thinkness of only 80 microns. It can also be layered and can withstand wash cycles up to 40° C.

APPLICATION TECHNIQUES

- Knockout
- Layering from other series

APPLICATION STEPS

- Cut 45° blade
- Weed excess material
- Turn on your heat press heat to 130°C/265°F
- Place your graphic on the garment
- Press it 130°C/265°F for 8 seconds
- Remove the liner hot

SIZES

H 50 cm	L	25 mt / 12,5 mt / 5 mt / 1 mt
H 75 cm	L	25 mt (upon request)
H 100 cm	L	25 mt (upon request)
H 150 cm	L	25 mt (upon request)

Comply with regulation REACH n°1907/2006/EU

TECHNICAL DATA



Film: PU/polyurethane



Thickness: 80µ (±5%)



Liner: adhesive PET



Finish: matte

PLOTTER SETTING



Cut settings: mirror



Blade: 45°



Minimum cut: 0,5 cm

APPLICATION



Temperature: 130°C - 265°F



Time: 8"



Liner removal: hot



Pressure: medium - 3,5 bar - 50 PSI



Textile: synthetic, sublimated fabrics

WASH RESISTANCE

First wash after application	wait 12 hours
Max wash temperature	40°C - 104°F
Dry clean	×
Dryer	×

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

Rev_2021/03

follow us















COLOUR GUIDE



- Ultra thin!
- Prevents the color's pigmentations from migrating from the fabric to the film's surface
- Fully opaque



BF 700ASU80 WHITE SUBLISTOP (80μ)

